



### WATER-COOLED CHILLER SPECIFICATIONS

MODEL NO.	HP/TONS	NOMINAL BTUH	VOLTS / PHASE	AMPS.	WATTS	L	W	H	W2	WO	WI	R134A REFRIGERANT CHARGE (OZ.)	*CITY WATER USE (GPM)	WC WATER IN/OUT (FPT)	WATER FLOW RATE (GPM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
DS-3WC	1/4	3,080	115	5.4	621	19"	12"	11"	2"	7 1/2"	3 1/2"	5	.3	3/4	8-15	60	65	26x16x16
DS-4WC	1/3	4,050	115	7.2	828	22 1/2"	13"	11"	2"	7 1/2"	3 1/2"	8	.5	3/4	10-20	66	69	29x18x16
DS-5WC	1/2	6,000	115	9.5	1092	24"	15 1/2"	13"	3"	9"	4"	9.5	.7	1 1/2	12-25	100	119	33x26x25
DS-6WC	1/2	6,000	230/1	4.8	1104	24"	15 1/2"	13"	3"	9"	4"	9.5	.7	1 1/2	12-25	100	119	33x26x25

\* CITY WATER USE BASED ON 55-60°F WATER TEMPERATURE ENTERING THE UNIT. WATER FLOWS THROUGH UNIT ONLY WHEN THE UNIT IS RUNNING

ALL DIMENSIONS ARE APPROXIMATE AND CAN CHANGE WITHOUT NOTICE

 Aqua Logic, Inc.  
8268 Clairemont Mesa Blvd. Suite 302  
San Diego, CA 92111

TITLE: DS-3WC THRU DS-6WC  
WATER-COOLED CHILLER  
SPECIFICATIONS

LAST UPDATE: 10-16-07

DATE: 4-28-06

FILE: DS-3,4,5 & 6 WC SPEC

BY: CE