



HEAT EXCHANGER SPECIFICATIONS

COMPLETE CHILLER UNIT MODEL NO.	INDOOR HEAT EXCHANGER MODEL NO.	NOMINAL HP / BTUH / KW	DIMENSIONS (IN)			*PROCESS WATER MIN / MAX FLOW RATE (GPM)	REFRIGERANT CONNECTION SIZE HI / LOW (ODF)
			A	B	C		
MT-1 SPLIT	HX-24DX	2 / 24K / 7	17 1/2	18 1/2	28	20 / 40	3/8" / 5/8"
MT-3 SPLIT	HX-36DX	3 / 36K / 10.5	25	26	35	20 / 40	3/8" / 5/8"
MT-5 SPLIT	HX-48DX	4 / 48K / 14	32 1/2	33 1/2	43	30 / 60	3/8" / 1 1/8"
MT-8 SPLIT	HX-60DX	5 / 60K / 17.5	40	41	50	30 / 60	3/8" / 1 1/8"

\*NOTE: FOR WATER TEMPERATURE 55 °F AND BELOW WATER FLOW RATE MUST BE CLOSE TO THE MAXIMUM.

OPTIONS: SCH 80 AND CPVC MATERIAL SHELL CONSTRUCTION  
316 STAINLESS STEEL STAND AND HARDWARE

**aqualogic**  
Aqua Logic, Inc.  
8268 Clairemont Mesa Blvd. Suite 302  
San Diego, CA 92111

TITLE: HX-24DX THRU  
HX-60DX HEAT  
EXCHANGERS

LAST UPDATE: 4-22-08

DATE: 1-5-06

FILE: HX-24 thru 60DX v4-22-08

BY: CE