



AQUA LOGIC WATER TO WATER HEAT EXCHANGERS									
MODEL NO.	NOMINAL BTUH / KW	PROCESS WATER IN/OUT	PROCESS WATER MAX. FLOW RATE (GPM)	COLD/HOT WATER SUPPLY IN/OUT	COLD/HOT WATER FLOW RATE (GPM)*	DIM A	DIM B	DIM C	DIM D
HX-24W	24K/7	2" SLIP	40	1/2" FPT	5 / 2.5	26"	24"	14"	14.5"
HX-36W	36K/10.5	2" SLIP	40	3/4" FPT	7 / 3.5	41"	32"	21"	21.5"
HX-48W	48K/14	2" SLIP	60	3/4" FPT	10 / 5	49"	40"	29"	29.5"
HX-60W	60K/17.5	2" SLIP	60	3/4" FPT	12 / 6	55"	47"	36"	36.5"

*FLOW RATE (GPM) IS BASED ON 40 °F EWT @ 10 °F ΔT (COLD) OR 180 °F EWT @ 20 °F ΔT (HOT) WATER SUPPLY

NOTE: COLD OR HOT WATER CONNECTIONS MAY OR MAY NOT CHANGE DUE TO VARIOUS FLOW RATE CONDITIONS

OPTIONS: SCH 80 AND CPVC MATERIAL SHELL CONSTRUCTION
 316 STAINLESS STEEL STAND
 316 STAINLESS STEEL HARDWARE

 Aqua Logic, Inc.
 8268 Clairemont Mesa Blvd. Suite 302
 San Diego, CA 92111

TITLE: HX-24W thru 60W Heat exchangers

LAST UPDATE: 3-19-07

DATE: 11-13-02

FILE:HX-24 thru 60W cut sheet rev2

BY CE