



AQUA LOGIC WATER TO WATER HEAT EXCHANGERS							
MODEL NO.	NOMINAL BTUH / KW	PROCESS WATER IN/OUT	PROCESS WATER FLOW RATE (GPM)	COLD/HOT WATER SUPPLY IN/OUT	COLD/HOT WATER FLOW RATE (GPM)*	DIM A	DIM B
HX-3W	3K / .9	3/4" FPT	15	1/2" FPT	.6 / .3	13"	12"
HX-4W	4K / 1.1	3/4" FPT	20	1/2" FPT	.8 / .4	14"	12"
HX-6W	6K / 1.7	1 1/2" FPT	25	1/2" FPT	1.2 / .6	16"	12"
HX-9W	9K / 2.6	1 1/2" FPT	30	1/2" FPT	1.8 / .9	22"	14 1/2"
HX-12W	12K / 3.5	1 1/2" FPT	35	1/2" FPT	2.4 / 1.2	24"	17 1/2"

*FLOW RATE (GPM) IS BASED ON 40 °F EWT @ 10 °F ΔT (COLD) OR 180 °F EWT @ 20 °F ΔT (HOT) WATER SUPPLY

ALL DIMENSIONS ARE A APPROXIMATION AND CAN BE CHANGE AT ANY TIME.

NOTE: COLD OR HOT WATER CONNECTIONS MAY OR MAY NOT CHANGE DUE TO VARIOUS FLOW RATE CONDITIONS

OPTIONS: SCH 80 AND CPVC MATERIAL SHELL CONSTRUCTION
316 STAINLESS STEEL STAND
316 STAINLESS STEEL HARDWARE

 Aqua Logic, Inc.
8268 Clairemont Mesa Blvd. Suite 302
San Diego, CA 92111

TITLE: HX-3W thru 12W
HEAT EXCHANGERS

LAST UPDATE: 3-15-07

DATE: 9-19-02

FILE: HX-3W thru 12W cut sheet rev2

BY CE