



50 PSI MAXIMUM WATER PRESSURE  
400 PSI MAXIMUM REFRIGERANT PRESSURE

HEAT EXCHANGER SPECIFICATIONS

OUTDOOR UNIT MODEL NO.	INDOOR EVAPORATOR MODEL NO.	NOMINAL BTUH/TONS/KW	REFRIGERANT CONNECTIONS NO. OF CIRCUITS INLET/OUTLET (ODF)	WATER FLOW MIN*/MAX (GPM)	DIM "H"	DIM "CL"
MT-9	HX-90-DX	96K / 7.5 / 28	1 @ 1/2" / 1 3/8"	90/180	60	54
MT-10	HX-120-DX	120K / 10 / 35	1 @ 1/2" / 1 3/8"	90/180	66	60
MT-12	HX-150-DX	150K / 12.5 / 44	2 @ 3/8" / 1 1/8"	90/180	72	66
MT-15	HX-180-DX	175K / 15 / 51.2	1 @ 5/8" / 1 5/8"	90/180	80	72
MT-20	HX-240-DX	223K / 20 / 65.3	2 @ 1/2" / 1 3/8"	90/180	88	82

\* MINIMUM FLOW RATE AT 65 F AND ABOVE. AT 65 F AND BELOW 120 GPM MINIMUM

ALL DEMINSIONS ARE APPROXIMATIONS AND MAY CHANGE AT ANY TIME

OPTIONS: SCH 80 AND CPVC MATERIAL SHELL CONSTRUCTION  
316 STAINLESS STEEL STAND  
316 STAINLESS STEEL HARDWARE



TITLE: HX-90-DX THRU HX-240-DX HEAT EXCHANGERS